

IW-RA102

=Motherboard=

Brand	Model	CPU	Dimension
Intel	S1200BTL	Socket 1155	12" x 9.6"
Supermicro	X7SBL-LN1	Xeon	9.6" x 9.6"
Supermicro	X7SBL-LN2	Xeon	9.6" x 9.6"
Supermicro	X7SBL-LN4	Xeon	12" x 9.6"
Supermicro	X7SBL	Xeon	12" x 9.6"
Supermicro	X7SB3	Xeon	12" x 9.6"
Supermicro	X7SB3-F	Xeon	12" x 9.6"
ASUS	Z10PA-U8	Socket LGA 2011 V3	12" x 9.6"
ASUS	P9D-E	Socket LGA 2011	12" x 9.6"
ASUS	P9D-C	Socket LGA 2011	12" x 9.6"
ASUS	P9D-V	Socket LGA 2011	12" x 9.6"
ASUS	P9D-X	Socket LGA 2011	12" x 9.6"
ASUS	P9D-MV	Socket LGA 2011	9.6" x 9.6"
ASUS	P9D-M	Socket LGA 2011	9.6" x 9.6"
AsrockRack	EPC612D8A	Socket LGA 2011 R3	12" x 9.6"
AsrockRack	EPC612D8A-TB	Socket LGA 2011 R3	12" x 9.6"
AsrockRack	EPC612D8	Socket LGA 2011 R3	12" x 9.6"
AsrockRack	EPC602D8A	Socket LGA 2011	12" x 9.6"
AsrockRack	E3C224D4M-16RE	Socket LGA 1150	12" x 9.6"
AsrockRack	E3C224-4L	Socket LGA 1150	12" x 9.6"
AsrockRack	E3C224	Socket LGA 1150	12" x 9.6"
AsrockRack	E3C224-V4L	Socket LGA 1150	12" x 9.6"
AsrockRack	E3C224-V+	Socket LGA 1150	12" x 9.6"
AsrockRack	E3C204-4L	Socket LGA 1155	12" x 9.6"
AsrockRack	E3C204	Socket LGA 1155	12" x 9.6"
AsrockRack	E3C204-V4L	Socket LGA 1155	12" x 9.6"
AsrockRack	E3C204-V+	Socket LGA 1155	12" x 9.6"
AsrockRack	E3C226D2I	Socket LGA 1150	6.7" x 6.7"
AsrockRack	E3C224D4I-14S	Socket LGA 1150	6.7" x 6.7"
AsrockRack	E3C224D2I	Socket LGA 1150	6.7" x 6.7"
AsrockRack	MT-C224	Socket LGA 1150	6.7" x 6.7"

AsrockRack	C2750D4I	Intel Avoton C2750 Octa-Core Processor	6.7" x 6.7"
AsrockRack	C2550D4I	Intel Avoton C2550 Quad-Core Processor	6.7" x 6.7"
AsrockRack	AD2550R/U3S3	Intel® Dual-Core Atom D2550 Processor	6.7" x 6.7"



Note:

- * The listed components had been tested by In Win lab according to In Win's verification standard.
- * To avoid failure and errors, please also reference components vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.