

IW-RS110-07

=Motherboard=

Brand	Model	CPU Socket	Form Factor
ASROCKRACK	EP2C622D16NM	Socket-3647	EEB
SuperMicro	H11SSL-NC	Socket-4094 (SP3)	ATX

=CPU=

Brand	Model	CPU Socket	Form Factor	TDP
Intel®	Xeon® Platinum 8160	Socket-3647	Purley	150W
AMD	EPYC PS7451BDVHCAF 2.9GHz	Socket-4094	EPYC (SP3)	180W

=Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Seagate	ST9250610NS	SATA	2.5"	250GB	7200 RPM
Seagate	ST200FM0053	SAS SSD	2.5"	200GB	-
Intel®	SSD 730	SATA SSD	2.5"	450GB	-
Intel®	P750 800GB SSD	NVMe	2.5" 25W	800GB	-
WD	WD5000BPKX-75HPJT0	SATA	2.5"	500GB	7200 RPM

=RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9460-16i (16 port SAS/SATA)	Internal x 16 (NVMe x4)	SATA/SAS 12G	0,1,5,6,10,50,60

=Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	B4	Purley Narrow	Socket-3647	205W
Dynatron	B4A	Purley Narrow	Socket-3647	205W
Dynatron	A25	EPYC	socket-4094(SP3r2)	180W

Note:

- * The listed components had been tested by In Win lab according to In Win's verification standard.
- * To avoid failure and errors, please also reference components vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.